



## ➤ PRODUCT BULLETIN

# Cesa™ Fiber Additives for Heat Preservation

Today's lifestyle tends to be more focused on outdoor sports and long-distance travel, developing more functional clothing is the key for brand owners and OEMs.

Cesa™ Fiber Additives for heat preservation are the formulated additives to enhance the heat preservation performance of textiles with synthetic fibers according to the test standard GB/T 30127-2013. Fabrics made with Cesa Fiber Additives can absorb more heat when exposed to simulated sunlight with the wavelength from 320 to 1100nm. Photothermally active particles added to the fibers help transform the energy of invisible light rays into heat for enhanced comfort in cold temperatures. When exposed to a light source for 10 minutes, this new generation of heat-preservation additives can provide a temperature increase from 6°C to 12°C for PET and PA fibers based on different let-down-ratio and textile structure.

This solution includes two grades, one for polyamide and the other for polyester fibers. They also can be combined with specific colorants into a single, customized masterbatch.

### KEY CHARACTERISTICS

- Offers reheating property for synthetic fibers with specialty formulations
- Provides a temperature increase of up to 12°C when exposed to a light source for 10 minutes
- Good spinnability
- Lower impact on the color

### APPLICATIONS

Cesa Fiber Additives are intended for use in:

- Clothing: hoodie, sweater, jacket, ski clothing, thermal underwear, etc.
- Home textile: bedding, blankets, etc.
- Technical fabrics for thermal insulation



Customized hangtag service can be provided upon customers' requirements.

1.844.4AVIENT  
www.avient.com



Copyright © 2023, Avient Corporation. Avient makes no representations, guarantees, or warranties of any kind with respect to the information contained in this document about its accuracy, suitability for particular applications, or the results obtained or obtainable using the information. Some of the information arises from laboratory work with small-scale equipment which may not provide a reliable indication of performance or properties obtained or obtainable on larger-scale equipment. Values reported as "typical" or stated without a range do not state minimum or maximum properties; consult your sales representative for property ranges and min/max specifications. Processing conditions can cause material properties to shift from the values stated in the information. Avient makes no warranties or guarantees respecting suitability of either Avient's products or the information for your process or end-use application. You have the responsibility to conduct full-scale end-product performance testing to determine suitability in your application, and you assume all risk and liability arising from your use of the information and/or use or handling of any product. AVIENT MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, either with respect to the information or products reflected by the information. This literature shall NOT operate as permission, recommendation, or inducement to practice any patented invention without permission of the patent owner.