

**POLYONE CORPORATION****MATERIAL SAFETY DATA SHEET****STAN-TONE VC-27700 HP CAT BLUE 528**Version Number 1.4  
Revision Date 11/07/2013Page 1 of 7  
Print Date 11/7/2013**1. PRODUCT AND COMPANY IDENTIFICATION****POLYONE CORPORATION**  
33587 Walker Road, Avon Lake, OH 44012

Telephone : 1 (440) 930-1000 or 1 (866) POLYONE  
Emergency telephone : **CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure number or accident).**

Product name : STAN-TONE VC-27700 HP CAT BLUE 528  
Product code : CC10017849  
Chemical Name : Mixture  
CAS-No. : Mixture  
Product Use : Industrial Applications

**2. COMPOSITION/INFORMATION ON INGREDIENTS**

| Components        | CAS-No.    | Weight percent |
|-------------------|------------|----------------|
| Silica, amorphous | 7631-86-9  | 1 - 5          |
| Titanium dioxide  | 13463-67-7 | 30 - 60        |

**3. HAZARDS IDENTIFICATION****EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

**POTENTIAL HEALTH EFFECTS****Routes of Exposure:** : Inhalation, Skin contact, Ingestion**Acute exposure**

Inhalation : Resin particles, like other inert materials, can be mechanically irritating.  
Ingestion : May be harmful if swallowed.  
Eyes : Particulates, like other inert materials can be mechanically irritating.  
Skin : Experience shows no unusual dermatitis hazard from routine handling.

**Chronic exposure** : Refer to Section 11 for Toxicological Information.

**POLYONE CORPORATION****MATERIAL SAFETY DATA SHEET****STAN-TONE VC-27700 HP CAT BLUE 528**

Version Number 1.4

Revision Date 11/07/2013

Page 2 of 7

Print Date 11/7/2013

**Medical Conditions** : None known.  
**Aggravated by Exposure:**

**4. FIRST AID MEASURES**

**Inhalation** : Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.

**Ingestion** : Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.

**Eyes** : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.

**Skin** : Wash off with soap and plenty of water. If skin irritation persists seek medical attention.

**5. FIREFIGHTING MEASURES**

**Flash point** : not applicable

**Flammable Limits**

- Upper explosion limit : not applicable
- Lower explosion limit : not applicable

**Auto-ignition temperature** : Not relevant

**Suitable extinguishing media** : Carbon dioxide blanket, Water spray, Dry powder, Foam.

**Special Fire Fighting Procedures** : Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.

**Unusual Fire/Explosion Hazards** : May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions. Carbon dioxide (CO<sub>2</sub>), carbon monoxide (CO), oxides of nitrogen (NO<sub>x</sub>), other hazardous materials, and smoke are all possible.

**6. ACCIDENTAL RELEASE MEASURES**

**Personal precautions** : Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.

**Environmental precautions** : Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.

**Methods for cleaning up** : Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal.

**7. HANDLING AND STORAGE**

**Handling** : Take measures to prevent the build up of electrostatic charge. Heat

**POLYONE CORPORATION**

**MATERIAL SAFETY DATA SHEET**

**STAN-TONE VC-27700 HP CAT BLUE 528**

Version Number 1.4  
Revision Date 11/07/2013

Page 3 of 7  
Print Date 11/7/2013

only in areas with appropriate exhaust ventilation. Processing fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize accumulation of these materials.

Storage : Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

Respiratory protection : No personal respiratory protective equipment normally required. If dusty conditions occur wear appropriate respiratory protection.

Eye/Face Protection : Safety glasses with side-shields

Hand protection : Protective gloves

Skin and body protection : Long sleeved clothing

Additional Protective Measures : Safety shoes

General Hygiene Considerations : Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

Exposure limit(s)

**POLYONE CORPORATION**

**MATERIAL SAFETY DATA SHEET**

**STAN-TONE VC-27700 HP CAT BLUE 528**

Version Number 1.4

Revision Date 11/07/2013

Page 4 of 7

Print Date 11/7/2013

| Components        | Value     | Exposure time                     | Exposure type          | List:    |
|-------------------|-----------|-----------------------------------|------------------------|----------|
| Silica, amorphous | 6 mg/m3   | Recommended exposure limit (REL): |                        | NIOSH    |
|                   | 0.8 mg/m3 | Time Weighted Average (TWA):      |                        | Z3       |
|                   | 10 mg/m3  | Time Weighted Average (TWA):      | Inhalable particulate. | MX OEL   |
|                   | 3 mg/m3   | Time Weighted Average (TWA):      | Respirable dust.       | MX OEL   |
| Titanium dioxide  | 10 mg/m3  | Time Weighted Average (TWA):      |                        | ACGIH    |
|                   | 15 mg/m3  | PEL:                              | Total dust.            | OSHA Z1  |
|                   | 10 mg/m3  | Time Weighted Average (TWA):      | Total dust.            | OSHA Z1A |
|                   | 10 mg/m3  | Time Weighted Average (TWA):      | as Ti                  | MX OEL   |
|                   | 20 mg/m3  | Short Term Exposure Limit (STEL): | as Ti                  | MX OEL   |

**9. PHYSICAL AND CHEMICAL PROPERTIES**

|                     |                    |                  |                  |
|---------------------|--------------------|------------------|------------------|
| Form                | : solid            | Evaporation rate | : Not applicable |
| Appearance          | : powder, granular | Specific Gravity | : Not determined |
| Colour              | : BLUE             | Bulk density     | : Not determined |
| Odour               | : very faint       | Vapour pressure  | : not applicable |
| Melting point/range | : Not determined   | Vapour density   | : not applicable |
| Boiling Point:      | : not applicable   | pH               | : not applicable |
| Water solubility    | : insoluble        |                  |                  |

**10. STABILITY AND REACTIVITY**

|                                  |   |
|----------------------------------|---|
| Stability                        | : The product is stable if stored and handled as prescribed.  |
| Hazardous Polymerization         | : Will not occur.   |
| Conditions to avoid              | : To avoid thermal decomposition, do not overheat. Keep away from oxidizing agents and open flame.  |
| Incompatible Materials           | : Incompatible with strong acids and oxidizing agents., Avoid contact with acetal homopolymers and acetal copolymers during processing.   |
| Hazardous decomposition products | : Carbon dioxide (CO <sub>2</sub> ), carbon monoxide (CO), oxides of nitrogen (NO <sub>x</sub> ), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating (approximately 30 minutes or more) above 392 °F (200 °C) or short term heating at 482 °F (250 °C) may result in product decomposition and evolution of carbon monoxide and hydrogen chloride. |

**11. TOXICOLOGICAL INFORMATION**

**POLYONE CORPORATION****MATERIAL SAFETY DATA SHEET****STAN-TONE VC-27700 HP CAT BLUE 528**

Version Number 1.4

Revision Date 11/07/2013

Page 5 of 7

Print Date 11/7/2013

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

| CAS-No.    | Chemical Name     | Effect           | Target Organ              |
|------------|-------------------|------------------|---------------------------|
| 7631-86-9  | Silica, amorphous | Irritant         | Eyes, Respiratory system. |
| 13463-67-7 | Titanium dioxide  | Systemic effects | Respiratory system.       |

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

| CAS-No.    | Chemical Name    | OSHA | IARC | NTP |
|------------|------------------|------|------|-----|
| 13463-67-7 | Titanium dioxide | no   | 2B   | no  |

IARC Carcinogen Classifications:

- 1 - The component is carcinogenic to humans.
- 2A - The component is probably carcinogenic to humans.
- 2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

- 1 - The component is known to be a human carcinogen.
- 2 - The component is reasonably anticipated to be a human carcinogen.

**12. ECOLOGICAL INFORMATION**

- Persistence and degradability : Not readily biodegradable.
- Environmental Toxicity : Adverse ecological impact is not known or expected under normal use.
- Bioaccumulation Potential : no data available
- Additional advice : no data available

**13. DISPOSAL CONSIDERATIONS**

- Product : Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
- Contaminated packaging : Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.

**POLYONE CORPORATION**

**MATERIAL SAFETY DATA SHEET**

**STAN-TONE VC-27700 HP CAT BLUE 528**

Version Number 1.4  
Revision Date 11/07/2013

Page 6 of 7  
Print Date 11/7/2013

**14. TRANSPORT INFORMATION**

U.S. DOT Classification : Not classified as dangerous good under transport regulations.  
ICAO/IATA : Not classified as dangerous good under transport regulations.  
IMO/IMDG (maritime) : Not classified as dangerous good under transport regulations.

**15. REGULATORY INFORMATION**

US Regulations:

OSHA Status : Classified as hazardous based on components.  
TSCA Status : All components of this product are listed on or exempt from the TSCA Inventory.

US. EPA CERCLA Hazardous Substances (40 CFR 302)

not applicable

California Proposition 65 : WARNING! This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Canadian Regulations:

National Pollutant Release Inventory (NPRI)

| Chemical Name       | CAS-No.  | Weight percent | NPRI ID# |
|---------------------|----------|----------------|----------|
| Phthalocyanine blue | 147-14-8 | 10.00 - 30.00  |          |

WHMIS Classification : D2A

**POLYONE CORPORATION**

**MATERIAL SAFETY DATA SHEET**

**STAN-TONE VC-27700 HP CAT BLUE 528**

Version Number 1.4  
Revision Date 11/07/2013

Page 7 of 7  
Print Date 11/7/2013

WHMIS Ingredient Disclosure List

|           |
|-----------|
| CAS-No.   |
| 147-14-8  |
| 7631-86-9 |
| 513-77-9  |

DSL : All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

Australia AICS : Not determined  
China IECS : Not determined  
Europe EINECS : Listed  
Japan ENCS : Not determined  
Korea KECI : Not determined  
Philippines PICCS : Not determined

**16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.