

MATERIAL SAFETY DATA SHEET

RT3890MS YELLOW 6287

Version Number 1.0
Revision Date 02/17/2002

Page 1 of 7
Print Date 11/3/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION
33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE : Product Stewardship (440)-930-1395
Emergency telephone number : **CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).**

Product name : RT3890MS YELLOW 6287
Product code : EM10000275
Chemical Name : Mixture
CAS-No. : Mixture
Product Use : Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

| Components | CAS-No. | Weight % |
|---------------------------------------|-----------|----------|
| Chrome yellow (Lead chromate pigment) | 1344-37-2 | 1 - 5 |
| Silica, amorphous | 7631-86-9 | 1 - 5 |

3. HAZARDS IDENTIFICATION
EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some fumes may be released upon heating or crosslinking and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect his employee from exposure. See Sections 3 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure: : Inhalation, Ingestion, Skin contact

Acute exposure

Inhalation : Resin particles, like other inert materials, can be mechanically irritating.
Ingestion : May be harmful if swallowed.
Eyes : Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin : Experience shows no unusual dermatitis hazard from routine handling.

Chronic exposure : Refer to Section 11 for Toxicological Information.

Medical Conditions : None known.

Aggravated by Exposure:

RT3890MS YELLOW 6287

Version Number 1.0

Page 2 of 7

Revision Date 02/17/2002

Print Date 11/3/2011

4. FIRST AID MEASURES

- Inhalation : Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
- Ingestion : Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
- Eyes : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
- Skin : Wash off with soap and plenty of water. If skin irritation persists seek medical attention.

5. FIRE-FIGHTING MEASURES

- Flash point : Not applicable
- Flammable Limits
 Upper explosion limit : Not applicable
 Lower explosion limit : Not applicable
- Autoignition temperature : Not relevant
- Suitable extinguishing media : Carbon dioxide blanket, Water spray, dry powder, foam.
- Special Fire Fighting Procedures : Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
- Unusual Fire/Explosion Hazards : None

6. ACCIDENTAL RELEASE MEASURES

- Personal precautions : Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
- Environmental precautions : Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
- Methods for cleaning up : Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.

7. HANDLING AND STORAGE

- Handling : Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
- Storage : Keep containers dry and tightly closed to avoid moisture absorption

MATERIAL SAFETY DATA SHEET

RT3890MS YELLOW 6287

Version Number 1.0

Page 3 of 7

Revision Date 02/17/2002

Print Date 11/3/2011

and contamination. Keep in a dry, cool place.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

- Respiratory protection : No personal respiratory protective equipment normally required.
- Eye/Face Protection : Safety glasses with side-shields.
- Hand protection : Protective gloves.
- Skin and body protection : Long sleeved clothing.
- Additional Protective Measures : Safety shoes.
- General Hygiene Considerations : Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
- Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

Exposure limit(s)

| Components | Value | Exposure time | Exposure type | List: |
|---------------------------------------|------------|------------------------------|---------------|---------|
| Chrome yellow (Lead chromate pigment) | 0.10 mg/m3 | Time Weighted Average (TWA): | as Cr | OSHA Z2 |
| | 0.01 mg/m3 | Time Weighted Average (TWA): | as Cr | ACGIH |
| | 1 mg/m3 | PEL: | as Cr | OSHA Z1 |
| | 0.05 mg/m3 | Time Weighted Average (TWA): | as Pb | ACGIH |
| | 0.05 mg/m3 | Time Weighted Average (TWA): | as Pb | OSHA |
| | 0.03 mg/m3 | OSHA Action level: | as Pb | OSHA |
| Silica, amorphous | 20 mppcf | PEL: | Total dust. | OSHA |
| | 20 mppcf | PEL: | Total dust. | Z3 |

9. PHYSICAL AND CHEMICAL PROPERTIES

- | | | | |
|---------------------|------------------|------------------|-------------------|
| Form | : Solid | Evaporation rate | : Not applicable. |
| Appearance | : Pellets, slabs | Specific Gravity | : Not determined |
| Color | : YELLOW | Bulk density | : Not established |
| Odor | : Very faint | Vapor pressure | : Not applicable |
| Melting point/range | : Not determined | Vapor density | : Not applicable |
| Boiling Point: | : Not applicable | pH | : Not applicable |
| Water solubility | : Insoluble | | |

10. STABILITY AND REACTIVITY

MATERIAL SAFETY DATA SHEET

RT3890MS YELLOW 6287

Version Number 1.0

Page 4 of 7

Revision Date 02/17/2002

Print Date 11/3/2011

| | | |
|----------------------------------|---|--|
| Stability | : | Stable. |
| Hazardous Polymerization | : | Will not occur. |
| Conditions to avoid | : | Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat. |
| Incompatible Materials | : | Incompatible with strong acids and oxidizing agents. |
| Hazardous decomposition products | : | Carbon dioxide (CO ₂), carbon monoxide (CO), oxides of nitrogen (NO _x), other hazardous materials, and smoke are all possible. |

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

| CAS-No. | Chemical Name | Effect | Target Organ |
|-----------|---------------------------------------|------------------|--|
| 1344-37-2 | Chrome yellow (Lead chromate pigment) | Systemic effects | central nervous system, reproductive system. |
| 7631-86-9 | Silica, amorphous | Irritant | Eyes, Respiratory system. |

Carcinogenicity:

This product contains the following components which in their pure form have the following carcinogenicity data:

| CAS-No. | Chemical Name | OSHA | IARC | NTP |
|-----------|---------------------------------------|------|------|-----|
| 1344-37-2 | Chrome yellow (Lead chromate pigment) | no | 1 | 1 |

IARC Carcinogen Classifications:

- 1 - The component is carcinogenic to humans.
- 2A - The component is probably carcinogenic to humans.
- 2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

- 1 - The component is known to be a human carcinogen.
- 2 - The component is reasonably anticipated to be a human carcinogen.

Additional Health Hazard Information:

Chrome yellow (Lead chromate pigment) 1344-37-2 Systemic effects include neurotoxic, teratogenic, fetotoxic and reproductive with abdominal pain, anemia, pallor, decreased hand grip strength with characteristic "wrist drop".

12. ECOLOGICAL INFORMATION

MATERIAL SAFETY DATA SHEET

RT3890MS YELLOW 6287

Version Number 1.0

Page 5 of 7

Revision Date 02/17/2002

Print Date 11/3/2011

| | | |
|-------------------------------|---|---|
| Persistence and degradability | : | Not readily biodegradable. |
| Environmental Toxicity | : | Chemicals are not readily available as they are bound within the matrix of the polymer. |
| Bioaccumulation Potential | : | Chemicals are not readily available as they are bound within the matrix of the polymer. |
| Additional advice | : | Not applicable |

13. DISPOSAL CONSIDERATIONS

| | | |
|------------------------|---|---|
| Product | : | Like most thermoplastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. |
| Contaminated packaging | : | Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. |

14. TRANSPORT INFORMATION

| | | |
|--|---|-----------------------------------|
| U.S. D.O.T. / CA T.D.G. Classification (Non-bulk ground) | : | Not regulated for transportation. |
| ICAO/IATA | : | Not regulated for transportation. |
| IMO / IMDG | : | Not regulated for transportation. |

15. REGULATORY INFORMATION

US Regulations:

| | | |
|---------------------------|---|--|
| OSHA Status | : | Classified as hazardous based on components. |
| TSCA Status | : | All components of this product are listed on the TSCA inventory or are exempt. |
| California Proposition 65 | : | WARNING! This product contains a chemical known in the State of California to cause cancer., WARNING! This product contains a chemical known in the State of California to cause birth defects or other reproductive harm. |

SARA Title III Section 313 Toxic Chemicals:

| Chemical Name | CAS-No. | Weight % |
|---------------|---------|----------|
|---------------|---------|----------|

MATERIAL SAFETY DATA SHEET

RT3890MS YELLOW 6287

Version Number 1.0

Page 6 of 7

Revision Date 02/17/2002

Print Date 11/3/2011

| Chemical Name | CAS-No. | Weight % |
|--|------------|----------|
| CHROMIUM VI COMPOUNDS LEAD COMPOUNDS, INORGANIC | 1344-37-2 | 2.43 |
| CHROMIUM VI COMPOUNDS LEAD COMPOUNDS, INORGANIC | 7758-97-6 | 0.00 |
| LEAD COMPOUNDS, INORGANIC | 7446-14-2 | 0.00 |
| CHROMIUM VI COMPOUNDS LEAD COMPOUNDS, INORGANIC | 12656-85-8 | 0.00 |

Canadian Regulations:

WHMIS Classification : Not controlled.

WHMIS Ingredient Disclosure List

| |
|------------|
| CAS-No. |
| 1344-28-1 |
| 1309-64-4 |
| 71631-15-7 |
| 1344-37-2 |
| 7758-97-6 |
| 7446-14-2 |
| 12656-85-8 |
| 7631-86-9 |
| 1314-23-4 |

DSL : Listed.

National Inventories:

Australia AICS : Not determined.

China IECS : Not determined.

Europe EINECS : Not determined.

Japan ENCS : Not determined.

Korea KECI : Not determined.

Philippines PICCS : Not determined.

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

POLYONE CORPORATION



MATERIAL SAFETY DATA SHEET

RT3890MS YELLOW 6287

Version Number 1.0
Revision Date 02/17/2002

Page 7 of 7
Print Date 11/3/2011