

SAFETY DATA SHEET**11500W1 WILFLEX ONE LB WHITE**Version Number 1.3
Revision Date 12/02/2020Page 1 of 18
Print Date 12/03/2020**SAFETY DATA SHEET****11500W1 WILFLEX ONE LB WHITE****Section 1. Identification**

GHS product identifier : 11500W1 WILFLEX ONE LB WHITE
Chemical name : Mixture
CAS number : Mixture
Other means of identification : FO20036912
Product type : liquid

Relevant identified uses of the substance or mixture and uses advised against

Product use : Industrial applications. Plastics.

Supplier's details : **POLYONE CORPORATION**
33587 Walker Road, Avon Lake, OH 44012

1 (440) 930-1000 or 1 (866) POLYONE

Emergency telephone number (with hours of operation) : CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).

Section 2. Hazards identification

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. After handling, always wash hands thoroughly with soap and water.

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture : SKIN SENSITIZATION - Category 1
GERM CELL MUTAGENICITY - Category 2
TOXIC TO REPRODUCTION - Category 2

GHS label elements

SAFETY DATA SHEET

11500W1 WILFLEX ONE LB WHITE

Version Number 1.3
Revision Date 12/02/2020

Page 2 of 18
Print Date 12/03/2020

Hazard pictograms**Signal word****Hazard statements**

- : Warning
- : May cause an allergic skin reaction.
- : Suspected of causing genetic defects.
- : Suspected of damaging fertility or the unborn child.

Precautionary statements**Prevention****Response****Storage****Disposal****Supplemental label elements****Hazards not otherwise classified**

- : Not applicable.
- : Obtain special instructions before use. Wear protective gloves. Wear protective clothing. Wear eye or face protection. Avoid breathing vapor.
- : IF exposed or concerned: Get medical advice or attention. Wash contaminated clothing before reuse. IF ON SKIN: Wash with plenty of water.
- : Not applicable.
- : Dispose of contents and container in accordance with all local, regional, national and international regulations.
- : None known.
- : None known.
- : Not available.

| |
|--|
| Section 3. Composition/information on ingredients |
|--|

Substance/mixture**Chemical name****Other means of identification**

- : Mixture
- : Mixture
- : FO20036912

CAS number/other identifiers

| Ingredient name | % | CAS number |
|---|---------------|------------|
| Titanium dioxide | >= 25 - <= 50 | 13463-67-7 |
| Diphenyloxide-4,4'-disulfohydrazide | >= 1 - <= 3 | 80-51-3 |
| Silica, amorphous | >= 1 - <= 3 | 7631-86-9 |
| 2,4,4-Trimethyl-1,3-pentanediol diisobutyrate | >= 0.3 - <= 1 | 6846-50-0 |

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

SAFETY DATA SHEET**11500W1 WILFLEX ONE LB WHITE**

Version Number 1.3
Revision Date 12/02/2020

Page 3 of 18
Print Date 12/03/2020

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

| |
|--------------------------------------|
| Section 4. First aid measures |
|--------------------------------------|

Description of necessary first aid measures

- | | | |
|---------------------|---|---|
| Eye contact | : | Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention. |
| Inhalation | : | Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. |
| Skin contact | : | Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse. |
| Ingestion | : | Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. |

Most important symptoms/effects, acute and delayed**Potential acute health effects**

SAFETY DATA SHEET**11500W1 WILFLEX ONE LB WHITE**

Version Number 1.3
Revision Date 12/02/2020

Page 4 of 18
Print Date 12/03/2020

| | | |
|---------------------|---|---|
| Eye contact | : | No known significant effects or critical hazards. |
| Inhalation | : | No known significant effects or critical hazards. |
| Skin contact | : | May cause an allergic skin reaction. |
| Ingestion | : | No known significant effects or critical hazards. |

Over-exposure signs/symptoms

| | | |
|---------------------|---|--|
| Eye contact | : | No specific data. |
| Inhalation | : | Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations |
| Skin contact | : | Adverse symptoms may include the following: irritation redness reduced fetal weight increase in fetal deaths skeletal malformations |
| Ingestion | : | Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations |

Indication of immediate medical attention and special treatment needed, if necessary

| | | |
|-----------------------------------|---|---|
| Notes to physician | : | In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. |
| Specific treatments | : | No specific treatment. |
| Protection of first-aiders | : | No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. |

See toxicological information (Section 11)

| |
|--|
| Section 5. Fire-fighting measures |
|--|

Extinguishing media

| | | |
|---------------------------------------|---|---|
| Suitable extinguishing media | : | In case of fire, use water spray (fog), foam, dry chemical or CO ₂ . |
| Unsuitable extinguishing media | : | None known. |

| | | |
|---|---|---|
| Specific hazards arising from the chemical | : | In a fire or if heated, a pressure increase will occur and the container may burst. |
|---|---|---|

SAFETY DATA SHEET

11500W1 WILFLEX ONE LB WHITE

Version Number 1.3
Revision Date 12/02/2020

Page 5 of 18
Print Date 12/03/2020

- | | | |
|---|---|---|
| Hazardous thermal decomposition products | : | Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides sulfur oxides metal oxide/oxides |
| Special protective actions for fire-fighters | : | Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. |
| Special protective equipment for fire-fighters | : | Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. |
| Remark | : | Based on available data, the classification criteria are not met. |
| Remark | : | Based on available data, the classification criteria are not met. |

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

- | | | |
|------------------------------------|---|--|
| For non-emergency personnel | : | No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment. |
| For emergency responders | : | If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel". |
| Environmental precautions | : | Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). |

Methods and materials for containment and cleaning up

- | | | |
|--------------------|---|---|
| Small spill | : | Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor. |
| Large spill | : | Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non- |

SAFETY DATA SHEET**11500W1 WILFLEX ONE LB WHITE**

Version Number 1.3
Revision Date 12/02/2020

Page 6 of 18
Print Date 12/03/2020

combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

- | | |
|---|---|
| Protective measures | : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container. |
| Advice on general occupational hygiene | : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures. |
| Conditions for safe storage, including any incompatibilities | : Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store in a well-ventilated place. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. |

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

SAFETY DATA SHEET

11500W1 WILFLEX ONE LB WHITE

Version Number 1.3
Revision Date 12/02/2020

Page 7 of 18
Print Date 12/03/2020

| Ingredient name | Exposure limits |
|---|--|
| Titanium dioxide | OSHA PEL 1989 (1989-03-01) TWA 10 mg/m ³ Form: Total dust OSHA PEL (1993-06-30) TWA 15 mg/m ³ Form: Total dust ACGIH TLV (1996-05-18) TWA 10 mg/m ³ |
| Diphenyloxide-4,4'-disulfohydrazide | ACGIH TLV (2000-03-01) TWA 0.1 mg/m ³ Form: Inhalable fraction |
| Silica, amorphous | NIOSH REL (1994-06-01) TWA 6 mg/m ³ |
| 2,4,4-Trimethyl-1,3-pentanediol diisobutyrate | None. |

Appropriate engineering controls : If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

Skin protection

SAFETY DATA SHEET

11500W1 WILFLEX ONE LB WHITE

Version Number 1.3
Revision Date 12/02/2020

Page 8 of 18
Print Date 12/03/2020

| | |
|-------------------------------|--|
| Hand protection | : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. |
| Body protection | : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. |
| Other skin protection | : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. |
| Respiratory protection | : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. |

Section 9. Physical and chemical properties

Appearance

| | |
|---|--|
| Physical state | : liquid [Paste.] |
| Color | : WHITE |
| Odor | : Odorless. |
| Odor threshold | : Not available. |
| pH | : 4.0 - 7.5 [Conc. (% w/w): > 1 g/l] |
| Melting point | : < 54 °C (< 129 °F) |
| Boiling point | : > 350 °C (> 662 °F) |
| Flash point | : > 273.00 °C (> 523.40 °F) |
| Burning time | : Not available. |
| Burning rate | : Not available. |
| Evaporation rate | : not applicable |
| Flammability (solid, gas) | : Based on available data, the classification criteria are not met. |
| Lower and upper explosive (flammable) limits | : Lower: Based on available data, the classification criteria are not met. Upper: Based on available data, the classification criteria are not met. |

SAFETY DATA SHEET

11500W1 WILFLEX ONE LB WHITE

Version Number 1.3
Revision Date 12/02/2020

Page 9 of 18
Print Date 12/03/2020

| | | |
|---|---|--|
| Vapor pressure | : | < 1 mm Hg @ 100C |
| Vapor density | : | Heavier than air. |
| Relative density | : | 1.02 |
| Solubility | : | Not available. |
| Solubility in water | : | insoluble in water. |
| Partition coefficient: n-octanol/water | : | Not available. |
| Auto-ignition temperature | : | Based on available data, the classification criteria are not met. |
| Decomposition temperature | : | Not available. |
| SADT | : | Not available. |
| Viscosity | : | Dynamic: Not available. Kinematic: 20,000 - 40,000 mm ² /s |

Aerosol product

| | | |
|---|---|----------------|
| Heat of combustion | : | Not available. |
| Ignition distance | : | Not available. |
| Enclosed space ignition - Time equivalent | : | Not available. |
| Enclosed space ignition - Deflagration density | : | Not available. |
| Flame height | : | Not available. |
| Flame duration | : | Not available. |

| |
|---|
| Section 10. Stability and reactivity |
|---|

| | | |
|---|---|--|
| Reactivity | : | No specific test data related to reactivity available for this product or its ingredients. |
| Chemical stability | : | Stable under recommended storage and handling conditions (see Section 7). |
| Possibility of hazardous reactions | : | Under normal conditions of storage and use, hazardous reactions will not occur. |
| Conditions to avoid | : | Keep away from extreme heat and oxidizing agents. |
| Incompatible materials | : | Keep away from strong acids. Oxidizer. |
| Hazardous decomposition products | : | Under normal conditions of storage and use, hazardous decomposition products should not be produced. |

SAFETY DATA SHEET

11500W1 WILFLEX ONE LB WHITE

 Version Number 1.3
 Revision Date 12/02/2020

 Page 10 of 18
 Print Date 12/03/2020

Section 11. Toxicological information
Information on toxicological effects
Acute toxicity

| Product/ingredient name | Result | Species | Dose | Exposure |
|--|------------------------------------|------------|---------------|----------|
| Titanium oxide | | | | |
| | LC50 Inhalation Dusts and mists | Rat - Male | 6.82 Mg/l | 4 h |
| | LD50 Dermal | Rabbit | > 5,000 mg/kg | - |
| Benzenesulfonic acid, 4,4'-oxybis-, 1,1'-dihydrazide | | | | |
| | LD50 Oral | Rat | 2,300 mg/kg | - |

Conclusion/Summary : Mixture.Not fully tested.

Irritation/Corrosion

| Product/ingredient name | Result | Species | Score | Exposure | Observation |
|--|----------------------|------------|-------|----------|-------------|
| Titanium oxide | Skin - Mild irritant | Human | - | 72 hrs | - |
| Silica | Eyes - Mild irritant | Rabbit | - | 24 hrs | - |
| Propanoic acid, 2-methyl-, 1,1'-[2,2-dimethyl-1-(1-methylethyl)-1,3-propanediyl] ester | Skin - Mild irritant | Human | - | 504 hrs | - |
| | Skin - Mild irritant | Guinea pig | - | | - |

Conclusion/Summary

Skin : Mixture.Not fully tested.
Eyes : Mixture.Not fully tested.
Respiratory : Mixture.Not fully tested.

Sensitization
Conclusion/Summary

Skin : Mixture.Not fully tested.
Respiratory : Mixture.Not fully tested.

Mutagenicity

Conclusion/Summary : Mixture.Not fully tested.

Carcinogenicity

Conclusion/Summary : Mixture.Not fully tested.

SAFETY DATA SHEET

11500W1 WILFLEX ONE LB WHITE

Version Number 1.3
Revision Date 12/02/2020

Page 11 of 18
Print Date 12/03/2020

Classification

| Product/ingredient name | OSHA | IARC | NTP |
|-------------------------|------|------|-----|
| Titanium oxide | - | 2B | - |
| Silica | - | 3 | - |

Reproductive toxicity

Conclusion/Summary : Mixture.Not fully tested.

Teratogenicity

Conclusion/Summary : Mixture.Not fully tested.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on the likely routes of exposure : Not available.

Potential acute health effects

Eye contact : No known significant effects or critical hazards.
Inhalation : No known significant effects or critical hazards.
Skin contact : May cause an allergic skin reaction.
Ingestion : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : No specific data.
Inhalation : Adverse symptoms may include the following: reduced fetal weight, increase in fetal deaths, skeletal malformations
Skin contact : Adverse symptoms may include the following: irritation, redness, reduced fetal weight, increase in fetal deaths, skeletal malformations
Ingestion : Adverse symptoms may include the following: reduced fetal weight, increase in fetal deaths, skeletal malformations

Delayed and immediate effects and also chronic effects from short and long term exposure**Short term exposure**

SAFETY DATA SHEET**11500W1 WILFLEX ONE LB WHITE**

Version Number 1.3
Revision Date 12/02/2020

Page 12 of 18
Print Date 12/03/2020

Potential immediate effects : Not available.
Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.
Potential delayed effects : Not available.

Potential chronic health effects

Conclusion/Summary : Mixture. Not fully tested.

General : Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

Carcinogenicity : No known significant effects or critical hazards.

Mutagenicity : Suspected of causing genetic defects.

Teratogenicity : Suspected of damaging the unborn child.

Developmental effects : No known significant effects or critical hazards.

Fertility effects : Suspected of damaging fertility.

Numerical measures of toxicity**Acute toxicity estimates**

| Product/ingredient name | Oral | Dermal | Inhalation (gases) | Inhalation (vapors) | Inhalation (dusts and mists) |
|--|----------------|--------|--------------------|---------------------|------------------------------|
| 11500W1 WILFLEX ONE LB WHITE | 30,569.8 mg/kg | N/A | N/A | N/A | N/A |
| Titanium oxide | N/A | N/A | N/A | N/A | 6.82 Mg/l |
| Benzenesulfonic acid, 4,4'-oxybis-, 1,1'-dihydrazide | 500 mg/kg | N/A | N/A | N/A | N/A |

Other information : This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Section 12. Ecological information

SAFETY DATA SHEET

11500W1 WILFLEX ONE LB WHITE

Version Number 1.3
Revision Date 12/02/2020

Page 13 of 18
Print Date 12/03/2020

Toxicity

| Product/ingredient name | Result | Species | Exposure |
|-------------------------|---|----------------------------------|----------|
| Titanium oxide | | | |
| | Acute LC50 > 1,000 Mg/l Marine water | Fish - Fundulus heteroclitus | 96 h |
| | Acute LC50 3 Mg/l Fresh water | Crustaceans - Ceriodaphnia dubia | 48 h |
| | Acute LC50 6.5 Mg/l Fresh water | Daphnia - Daphnia pulex | 48 h |

Conclusion/Summary : Not available.

Persistence and degradability

Conclusion/Summary : Not available.

Bioaccumulative potential

| Product/ingredient name | LogPow | BCF | Potential |
|--|--------|----------|-----------|
| Benzenesulfonic acid, 4,4'-oxybis-, 1,1'-dihydrazide | - | 3.00 | low |
| Propanoic acid, 2-methyl-, 1,1'-[2,2-dimethyl-1-(1-methylethyl)-1,3-propanediyl] ester | - | 5,340.00 | high |

Mobility in soil

Soil/water partition coefficient (KOC) : Not available.

Other adverse effects : No known significant effects or critical hazards.

| |
|--|
| Section 13. Disposal considerations |
|--|

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging

SAFETY DATA SHEET**11500W1 WILFLEX ONE LB WHITE**

Version Number 1.3
Revision Date 12/02/2020

Page 14 of 18
Print Date 12/03/2020

should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

United States - RCRA Acute hazardous waste "P" List: Not listed

United States - RCRA Toxic hazardous waste "U" List: Not listed

Section 14. Transport information

| | | |
|-----------------------------------|---|---------------------------------------|
| U.S.DOT 49CFR Ground/Air/Water | : | Not regulated for transportation. |
| International Air ICAO/IATA | : | Consult mode specific transport rules |
| International Water IMO/IMDG | : | Consult mode specific transport rules |

Section 15. Regulatory information

| | | |
|--------------------------|---|--|
| U.S. Federal regulations | : | <p>United States - TSCA 12(b) - Chemical export notification: None of the components are listed.</p> <p>United States - TSCA 4(a) - Final Test Rules: Not listed</p> <p>United States - TSCA 4(a) - ITC Priority list: Not listed</p> <p>United States - TSCA 4(a) - Proposed test rules: Not listed</p> <p>United States - TSCA 4(f) - Priority risk review: Not listed</p> <p>United States - TSCA 5(a)2 - Final significant new use rules: Not listed</p> <p>United States - TSCA 5(a)2 - Proposed significant new use rules: Not listed</p> <p>United States - TSCA 5(e) - Substances consent order: Not listed</p> <p>United States - TSCA 6 - Final risk management: Not listed</p> <p>United States - TSCA 6 - Proposed risk management: Not listed</p> <p>United States - TSCA 8(a) - Chemical risk rules: Not listed</p> <p>United States - TSCA 8(a) - Dioxin/Furane precursor: Not listed</p> <p>United States - TSCA 8(a) - Chemical Data Reporting (CDR): Not determined</p> <p>United States - TSCA 8(a) - Preliminary assessment report (PAIR): Listed Diphenyloxide-4,4'-disulfohydrazide</p> |
|--------------------------|---|--|

SAFETY DATA SHEET

11500W1 WILFLEX ONE LB WHITE

Version Number 1.3
Revision Date 12/02/2020

Page 15 of 18
Print Date 12/03/2020

Poly(dimethylsiloxane)

United States - TSCA 8(c) - Significant adverse reaction (SAR):
Not listed

United States - TSCA 8(d) - Health and safety studies: Not listed
United States - EPA Clean water act (CWA) section 307 - Priority pollutants: Listed Acrylonitrile

United States - EPA Clean water act (CWA) section 311 - Hazardous substances: Listed

United States - EPA Clean air act (CAA) section 112 - Accidental release prevention - Flammable substances: Not listed

United States - EPA Clean air act (CAA) section 112 - Accidental release prevention - Toxic substances: Not listed

United States - Department of commerce - Precursor chemical:
Not listed

Clean Air Act Section 112(b) Hazardous Air Pollutants (HAPs) : Listed
Clean Air Act Section 602 Class I Substances : Not listed
Clean Air Act Section 602 Class II Substances : Not listed
DEA List I Chemicals (Precursor Chemicals) : Not listed
DEA List II Chemicals (Essential Chemicals) : Not listed

US. EPA CERCLA Hazardous Substances (40 CFR 302)

not applicable

SARA 311/312

Classification : SKIN SENSITIZATION - Category 1
GERM CELL MUTAGENICITY - Category 2
TOXIC TO REPRODUCTION - Category 2

Composition/information on ingredients

| Name | % | Classification |
|--|---------------|---|
| Titanium oxide | >= 25 - <= 50 | CARCINOGENICITY - Category 2 |
| Benzenesulfonic acid, 4,4'-oxybis-, 1,1'-dihydrazide | >= 1 - <= 3 | COMBUSTIBLE DUSTS ACUTE TOXICITY - oral - Category 4 SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A |

SAFETY DATA SHEET**11500W1 WILFLEX ONE LB WHITE**

Version Number 1.3
Revision Date 12/02/2020

Page 16 of 18
Print Date 12/03/2020

| | | |
|--|---------------|--|
| | | SKIN SENSITIZATION - Category 1 GERM CELL MUTAGENICITY - Category 2 |
| Silica | >= 1 - <= 3 | EYE IRRITATION - Category 2B |
| Propanoic acid, 2-methyl-, 1,1'-[2,2-dimethyl-1-(1-methylethyl)-1,3-propanediyl] ester | >= 0.3 - <= 1 | TOXIC TO REPRODUCTION - Category 2 |

Not applicable.

State regulations**Massachusetts**

: None of the components are listed.

New York

: None of the components are listed.

New Jersey

: The following components are listed:

Titanium dioxide

Diphenyloxide-4,4'-disulfohydrazide

Pennsylvania

: The following components are listed:

Titanium dioxide

Silica, amorphous

California Prop. 65

WARNING: This product can expose you to Titanium dioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

| Ingredient name | No significant risk level | Maximum acceptable dosage level |
|------------------|---------------------------|---------------------------------|
| Titanium dioxide | - | - |

United States inventory (TSCA 8b) : All components are active or exempted.

Canada inventory : All components are listed or exempted.

International regulations**Inventory list****Australia**

: Not determined.

Canada

: All components are listed or exempted.

China

: Not determined.

Europe inventory

: Not determined.

Japan

: Not determined.

SAFETY DATA SHEET

11500W1 WILFLEX ONE LB WHITE

Version Number 1.3
Revision Date 12/02/2020

Page 17 of 18
Print Date 12/03/2020

| | | |
|-------------------|---|--|
| New Zealand | : | Not determined. |
| Philippines | : | Not determined. |
| Republic of Korea | : | All components are listed or exempted. |
| Taiwan | : | Not determined. |
| Turkey | : | Not determined. |
| United States | : | All components are active or exempted. |

Section 16. Other information

Hazardous Material Information System (U.S.A.)

| | | |
|------------------|---|---|
| Health | * | 2 |
| Flammability | | 1 |
| Physical hazards | | 0 |
| | | |

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

History

| | | |
|--------------------------------|---|--|
| Date of printing | : | 12/03/2020 |
| Date of issue/Date of revision | : | 12/02/2020 |
| Date of previous issue | : | 06/26/2018 |
| Version | : | 1.3 |
| Key to abbreviations | : | ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Intermediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) UN = United Nations |
| References | : | Not available. |

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or



SAFETY DATA SHEET

11500W1 WILFLEX ONE LB WHITE

Version Number 1.3
Revision Date 12/02/2020

Page 18 of 18
Print Date 12/03/2020

completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Particularly this information may not be valid for such material used in conjunction with any other materials or in any process, unless specified in the text.