

SAFETY DATA SHEET

LX-FC-1002 CLEAR NITRILE FABRIC COATING

Version Number 1.0
Revision Date 12/05/2016

Page 1 of 17
Print Date 12/07/2016

SAFETY DATA SHEET

LX-FC-1002 CLEAR NITRILE FABRIC COATING

Section 1. Identification

GHS product identifier : LX-FC-1002 CLEAR NITRILE FABRIC COATING
 Chemical name : Mixture
 CAS number : Mixture
 Other means of identification : FO20040116
 Product type : liquid

Relevant identified uses of the substance or mixture and uses advised against

Product use : Industrial applications. Plastics.

Supplier's details : **POLYONE CORPORATION**
 1675 Navarre Road SW, Massillon,
 Ohio USA 44646

1 330 837 8679

Emergency telephone number (with hours of operation) : CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).

Section 2. Hazards identification

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. Some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. After handling, always wash hands thoroughly with soap and water.

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture : CARCINOGENICITY - Category 1A

GHS label elements

SAFETY DATA SHEET

LX-FC-1002 CLEAR NITRILE FABRIC COATING

Version Number 1.0
Revision Date 12/05/2016

Page 2 of 17
Print Date 12/07/2016

Hazard pictograms : 

Signal word : Danger

Hazard statements : May cause cancer.

Precautionary statements

General : Not applicable.

Prevention : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves. Wear eye or face protection. Wear protective clothing.

Response : IF exposed or concerned: Get medical attention.

Storage : Store in a well-ventilated place.

Disposal : Dispose of contents and container in accordance with all local, regional, national and international regulations.

Supplemental label elements : None known.

Hazards not otherwise classified : None known.

Section 3. Composition/information on ingredients

Substance/mixture : Mixture

Chemical name : Mixture

Other means of identification : FO20040116

CAS number/other identifiers

Ingredient name	%	CAS number
Ethyl alcohol	0.1 - 0.3	64-17-5

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

SAFETY DATA SHEET

**LX-FC-1002 CLEAR NITRILE FABRIC COATING**

Version Number 1.0
Revision Date 12/05/2016

Page 3 of 17
Print Date 12/07/2016

Description of necessary first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed**Potential acute health effects**

- Eye contact** : No known significant effects or critical hazards.
Inhalation : No known significant effects or critical hazards.
Skin contact : No known significant effects or critical hazards.
Ingestion : No known significant effects or critical hazards.

Over-exposure signs/symptoms

- Eye contact** : No specific data.
Inhalation : No specific data.
Skin contact : No specific data.

LX-FC-1002 CLEAR NITRILE FABRIC COATING

Version Number 1.0
Revision Date 12/05/2016

Page 4 of 17
Print Date 12/07/2016

Ingestion : No specific data.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

Specific treatments : No specific treatment.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures
Extinguishing media

Suitable extinguishing media : In case of fire, use water spray (fog), foam, dry chemical or CO₂.

Unsuitable extinguishing media : None known.

Specific hazards arising from the chemical : In a fire or if heated, a pressure increase will occur and the container may burst.

Hazardous thermal decomposition products : No specific data.

Special protective actions for fire-fighters : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures
Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate

LX-FC-1002 CLEAR NITRILE FABRIC COATING

Version Number 1.0
Revision Date 12/05/2016

Page 5 of 17
Print Date 12/07/2016

- ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage
Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands

SAFETY DATA SHEET


LX-FC-1002 CLEAR NITRILE FABRIC COATING

Version Number 1.0
Revision Date 12/05/2016

Page 6 of 17
Print Date 12/07/2016

and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

- : Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store in a well-ventilated place. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection
Control parameters
Occupational exposure limits

Ingredient name	Exposure limits
Ethyl alcohol	OSHA PEL 1989 (1989-03-01) PEL: Permissible Exposure Level 1,900 mg/m ³ 1,000 ppm OSHA PEL (1993-06-30) PEL: Permissible Exposure Level 1,900 mg/m ³ 1,000 ppm NIOSH REL (1994-06-01) Time Weighted Average (TWA) 1,900 mg/m ³ 1,000 ppm ACGIH TLV (2008-11-24) TLV-STEL: Threshold Limit Value - Short Time Exposure Level 1,000 ppm

- Appropriate engineering controls** : If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical

LX-FC-1002 CLEAR NITRILE FABRIC COATING

Version Number 1.0
Revision Date 12/05/2016

Page 7 of 17
Print Date 12/07/2016

- products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.
- Skin protection**
- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Section 9. Physical and chemical properties
Appearance

- Physical state** : liquid [liquid]
Color : NO PIGMENT
Odor : Not available.
Odor threshold : Not available.
pH : Not available.
Melting point : Not available.

SAFETY DATA SHEET


LX-FC-1002 CLEAR NITRILE FABRIC COATING

Version Number 1.0
Revision Date 12/05/2016

Page 8 of 17
Print Date 12/07/2016

Boiling point	: Not available.
Flash point	: Not available.
Burning time	: Not available.
Burning rate	: Not available.
Evaporation rate	: Not available.
Flammability (solid, gas)	: Not available.
Lower and upper explosive (flammable) limits	: Lower: Not available. Upper: Not available.
Vapor pressure	: Not available.
Vapor density	: Not available.
Relative density	: Not available.
Solubility	: Not available.
Solubility in water	: Not available.
Partition coefficient: n-octanol/water	: Not available.
Auto-ignition temperature	: Not available.
Decomposition temperature	: Not available.
SADT	: Not available.
Viscosity	: Dynamic: Not available. Kinematic: Not available.

Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: Stable under recommended storage and handling conditions (see Section 7).
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: Keep away from extreme heat and oxidizing agents.
Incompatible materials	: Keep away from strong acids. Oxidizer.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Information on toxicological effects

Acute toxicity

SAFETY DATA SHEET

LX-FC-1002 CLEAR NITRILE FABRIC COATING

Version Number 1.0
Revision Date 12/05/2016

Page 9 of 17
Print Date 12/07/2016

Product/ingredient name	Result	Species	Dose	Exposure
Ethyl alcohol				
	LD50 Oral	Rat	15,010 mg/kg	-
	LD50 Oral	Rat	7,000 mg/kg	-
	LD50 Oral	Rat	7,060 mg/kg	-
	LC50 Inhalation	Rat	20,000 ppm	10 h
	LC50 Inhalation	Rat	5.9 mg/l	6 h
	LC50 Inhalation	Rat	124.7 mg/l	4 h

Conclusion/Summary : Mixture.Not fully tested.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Ethyl alcohol	Eyes - Moderate irritant	Rabbit			-
	Skin - Mild irritant	Rabbit			-
	Skin - Moderate irritant	Rabbit		24 hrs	-
	Eyes - Severe irritant	Rabbit			-
	Eyes - Mild irritant	Rabbit		24 hrs	-
	Eyes - Moderate irritant	Rabbit		0.001 hrs	-

Conclusion/Summary

Skin : Mixture.Not fully tested.
Eyes : Mixture.Not fully tested.
Respiratory : Mixture.Not fully tested.

Sensitization
Conclusion/Summary

Skin : Mixture.Not fully tested.
Respiratory : Mixture.Not fully tested.

Mutagenicity

Conclusion/Summary : Mixture.Not fully tested.

Carcinogenicity

SAFETY DATA SHEET

LX-FC-1002 CLEAR NITRILE FABRIC COATING

Version Number 1.0
Revision Date 12/05/2016

Page 10 of 17
Print Date 12/07/2016

Conclusion/Summary : Mixture.Not fully tested.

Classification

Product/ingredient name	OSHA	IARC	NTP
Ethyl alcohol		1	

Reproductive toxicity

Conclusion/Summary : Mixture.Not fully tested.

Teratogenicity

Conclusion/Summary : Mixture.Not fully tested.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on the likely routes of exposure : Not available.

Potential acute health effects

Eye contact : No known significant effects or critical hazards.
Inhalation : No known significant effects or critical hazards.
Skin contact : No known significant effects or critical hazards.
Ingestion : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : No specific data.
Inhalation : No specific data.
Skin contact : No specific data.
Ingestion : No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure
Short term exposure

Potential immediate effects : Not available.

SAFETY DATA SHEET

LX-FC-1002 CLEAR NITRILE FABRIC COATING

Version Number 1.0
Revision Date 12/05/2016

Page 11 of 17
Print Date 12/07/2016

Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Potential chronic health effects

Conclusion/Summary : Mixture. Not fully tested.

General : No known significant effects or critical hazards.

Carcinogenicity : May cause cancer. Risk of cancer depends on duration and level of exposure.

Mutagenicity : No known significant effects or critical hazards.

Teratogenicity : No known significant effects or critical hazards.

Developmental effects : No known significant effects or critical hazards.

Fertility effects : No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Not available.

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
Ethyl alcohol			
	Acute LC50 13,480,000 µg/l Fresh water	Fish - Fish	96 h
	Acute LC50 42,000 µg/l Fresh water	Fish - Fish	96 h
	Acute LC50 11,000,000 µg/l Marine water	Fish - Fish	96 h
	Acute LC50 12,720 mg/l Fresh water	Fish - Fish	96 h
	Acute EC50 12,900.0 mg/l Fresh water	Fish - Fish	96 h
	Acute LC50 5,680 mg/l Fresh water	Aquatic invertebrates. Daphnia	48 h

SAFETY DATA SHEET

LX-FC-1002 CLEAR NITRILE FABRIC COATING

Version Number 1.0
Revision Date 12/05/2016

Page 12 of 17
Print Date 12/07/2016

	Acute EC50 2,000 µg/l Fresh water	Aquatic invertebrates. Daphnia	48 h
	Acute LC50 9,248,000 µg/l Fresh water	Aquatic invertebrates. Daphnia	48 h
	Acute LC50 25,500 µg/l Marine water	Aquatic invertebrates. Crustaceans	48 h
	Acute LC50 6,076,000 µg/l Fresh water	Aquatic invertebrates. Crustaceans	48 h
	Acute LC50 3,715,000 µg/l Fresh water	Aquatic invertebrates. Crustaceans	48 h
	Acute LC50 5,577,000 µg/l Fresh water	Aquatic invertebrates. Crustaceans	48 h
	Acute EC50 1,074 mg/l Fresh water	Aquatic invertebrates. Crustaceans	48 h
	Acute EC50 7,640 mg/l Fresh water	Aquatic invertebrates. Daphnia	48 h
	Acute EC50 1,580 mg/l Fresh water	Aquatic invertebrates. Daphnia	48 h
	Acute EC50 17.921 mg/l Marine water	Aquatic plants - Algae	96 h
	Acute NOEC 4.995 mg/l Marine water	Aquatic plants - Algae	4 d
	Acute NOEC 350 mg/l Fresh water	Aquatic plants - Algae	4 d
	Acute NOEC 14 mg/l Fresh water	Aquatic plants - Algae	4 d
	Acute NOEC 20 mg/l Fresh water	Aquatic plants - Algae	4 d
	Acute NOEC 50 mg/l Marine water	Aquatic plants - Algae	3 d
	Chronic NOEC 0.375 mg/l Fresh water	Fish - Fish	84 d
	Chronic NOEC 0.375 mg/l Fresh water	Fish - Fish	84 d
	Chronic NOEC 0.375 mg/l Fresh water	Fish - Fish	84 d
	Chronic NOEC 0.375 mg/l Fresh water	Fish - Fish	84 d
	Chronic NOEC 0.375 mg/l Fresh water	Fish - Fish	84 d
	Chronic NOEC 100 mg/l Fresh water	Aquatic invertebrates. Daphnia	21 d
	Chronic NOEC 100 mg/l Fresh water	Aquatic invertebrates. Daphnia	21 d

Conclusion/Summary : Not available.

Persistence and degradability

Conclusion/Summary : Not available.

SAFETY DATA SHEET


LX-FC-1002 CLEAR NITRILE FABRIC COATING

Version Number 1.0
Revision Date 12/05/2016

Page 13 of 17
Print Date 12/07/2016

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
Ethyl alcohol	-0.35	-	low

Mobility in soil

- Soil/water partition coefficient (KOC) : Not available.
Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

- Disposal methods** : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

United States - RCRA Acute hazardous waste "P" List: Not listed

United States - RCRA Toxic hazardous waste "U" List: Not listed

Section 14. Transport information

- U.S. DOT Classification : Not regulated for transportation.
ICAO/IATA : Consult mode specific transport rules
IMO/IMDG (maritime) : Consult mode specific transport rules

Section 15. Regulatory information

SAFETY DATA SHEET


LX-FC-1002 CLEAR NITRILE FABRIC COATING

Version Number 1.0
Revision Date 12/05/2016

Page 14 of 17
Print Date 12/07/2016

U.S. Federal regulations	<ul style="list-style-type: none"> : United States - TSCA 12(b) - Chemical export notification: None of the components are listed. United States - TSCA 4(a) - Final Test Rules: Not listed United States - TSCA 4(a) - ITC Priority list: Not listed United States - TSCA 4(a) - Proposed test rules: Not listed United States - TSCA 4(f) - Priority risk review: Not listed United States - TSCA 5(a)2 - Final significant new use rules: Not listed United States - TSCA 5(a)2 - Proposed significant new use rules: Not listed United States - TSCA 5(e) - Substances consent order: Not listed United States - TSCA 6 - Final risk management: Not listed United States - TSCA 6 - Proposed risk management: Not listed United States - TSCA 8(a) - Chemical risk rules: Not listed United States - TSCA 8(a) - Dioxin/Furane precursor: Not listed United States - TSCA 8(a) - Chemical Data Reporting (CDR): Not determined United States - TSCA 8(a) - Preliminary assessment report (PAIR): Not listed United States - TSCA 8(c) - Significant adverse reaction (SAR): Not listed United States - TSCA 8(d) - Health and safety studies: Not listed United States - EPA Clean water act (CWA) section 307 - Priority pollutants: Listed Zinc oxide United States - EPA Clean water act (CWA) section 311 - Hazardous substances: Listed United States - EPA Clean air act (CAA) section 112 - Accidental release prevention - Flammable substances: Not listed United States - EPA Clean air act (CAA) section 112 - Accidental release prevention - Toxic substances: Not listed United States - Department of commerce - Precursor chemical: Not listed
Clean Air Act Section 112(b) Hazardous Air Pollutants (HAPs)	<ul style="list-style-type: none"> : Not listed
Clean Air Act Section 602 Class I Substances	<ul style="list-style-type: none"> : Not listed
Clean Air Act Section 602 Class II Substances	<ul style="list-style-type: none"> : Not listed
DEA List I Chemicals (Precursor Chemicals)	<ul style="list-style-type: none"> : Not listed
DEA List II Chemicals (Essential Chemicals)	<ul style="list-style-type: none"> : Not listed

SAFETY DATA SHEET

LX-FC-1002 CLEAR NITRILE FABRIC COATING

Version Number 1.0
Revision Date 12/05/2016

Page 15 of 17
Print Date 12/07/2016

US. EPA CERCLA Hazardous Substances (40 CFR 302)

not applicable

SARA 311/312

Classification : Delayed (chronic) health hazard

Composition/information on ingredients

Name	%	Classification
Ethyl alcohol	0.1 - 0.3	F, AH, CH

SARA 313

Not applicable.

State regulations

Massachusetts : None of the components are listed.
New York : None of the components are listed.
New Jersey : The following components are listed:
 Ethyl alcohol
Pennsylvania : The following components are listed:
 Ethyl alcohol

California Prop. 65

This PolyOne product does not contain any chemical known to the State of California to cause cancer, or birth defects or other reproductive harm, in concentrations that require a warning notice under California's Proposition 65. This statement relies in part on information provided by the buyer of this PolyOne product. PolyOne does not control or have complete knowledge of the end uses to which that buyer or any other entity in the chain of distribution and marketing may put this PolyOne product. Therefore, the buyer of this PolyOne product, each entity that uses this PolyOne product in formulating another product, and each entity in the chain of distribution and marketing of any product that includes the material in this PolyOne product must make its own decision as to giving a Proposition 65 warning.

United States inventory (TSCA 8b) : All components are listed or exempted.

Canada inventory : Not determined.

International regulations

International lists :

- Australia inventory (AICS):** Not determined.
- Taiwan Chemical Substances Inventory (TCSI):** Not determined.
- Malaysia Inventory (EHS Register):** Not determined.
- EINECS:** Not determined.
- Japan inventory:** Not determined.
- China inventory (IECSC):** Not determined.
- Korea inventory:** Not determined.

SAFETY DATA SHEET

LX-FC-1002 CLEAR NITRILE FABRIC COATING

Version Number 1.0
Revision Date 12/05/2016

Page 16 of 17
Print Date 12/07/2016

New Zealand Inventory of Chemicals (NZIoC): Not determined.
Philippines inventory (PICCS): Not determined.

Chemical Weapons Convention List Schedule I Chemicals : Not listed
Chemical Weapons Convention List Schedule II Chemicals : Not listed
Chemical Weapons Convention List Schedule III Chemicals : Not listed

Section 16. Other information
Hazardous Material Information System (U.S.A.) :

Health	*	0
Flammability		0
Physical hazards		0

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868. The customer is responsible for determining the PPE code for this material.

History

Date of printing : 12/07/2016
Date of issue/Date of revision : 12/05/2016
Date of previous issue : 00/00/0000
Version : 1.0

Key to abbreviations

ATE = Acute Toxicity Estimate
BCF = Bioconcentration Factor
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
IATA = International Air Transport Association
IBC = Intermediate Bulk Container
IMDG = International Maritime Dangerous Goods
LogPow = logarithm of the octanol/water partition coefficient
MARPOL 73/78 = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
UN = United Nations

References : Not available.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-

SAFETY DATA SHEET



LX-FC-1002 CLEAR NITRILE FABRIC COATING

Version Number 1.0
Revision Date 12/05/2016

Page 17 of 17
Print Date 12/07/2016

named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Particularly this information may not be valid for such material used in conjunction with any other materials or in any process, unless specified in the text.